

General tolerance
Cross-sectional direction
6 or below $\pm 0.5$
6 to 15 or below $\pm 0.6$
15 to 30 or below $\pm 0.8$
30 to 50 or below $\pm 0.9$
Longitudinal direction
120 or below $\pm 1.2$
120 to 400 or below $\pm 2.5$
400 to 1000 or below $\pm 5.0$

7-φ4.2 (Hole)

50 150 150 150 150 150 150 <50>

Rear View (1/5)

3D image

1000<sup>+0</sup><sub>-6</sub>

<50>

Screw hole: 7-φ4.2

50<sup>+0</sup><sub>-6</sub>

900 (=P150x6)

7.9

18.3

Note  
Screws are not included with the Channel

Installation for the light product

- Please mount FJS00-22 using screw in the screw hole to properly secure it.

For vertical light appliance installation

- Please attach FJS00-22 with L bracket near the end of the light product in order to prevent displacement.

		1	Polycarbonate (clear)
	Parts List	Quantity	Material / Processing
Remarks			
		Model	Tape Light
		Product Name	Polycarbonate Rigid Channel
		Product Number	FJS00-22
Scale	Drawn	Reviser	Approved
1 : 1 (A4 size)	Yamaguchi	Sakamoto	Tanimizu
	Jan 15 , 2020	Mar. 3 . 2025	Mar. 3 . 2025

(Unit : mm)