

Product Name	Tsubaki Seamless Light Type V Addressable						Scale	1:2 (A4)																																																																																																																																																																																
<div><div><div><div><div>Product No.</div><div>Length</div></div><div>TLD10-ADR-F</div><div>L = 114 ~ 1026 + 10mm</div></div><div><div>TLD10-ADR-S</div><div>L = 114 ~ 1026 + 10mm</div></div><div><div>TLD10-ADR-L</div><div>L = 171 ~ 1026 + 10mm</div></div></div><div>=</div><div><div>Basic Length</div><div>57mm (6LEDs)</div><div>114mm (12LEDs)</div><div>171mm (18LEDs)</div></div><div>X</div><div><div>Multiple Number of basic length</div><div>2 ~ 18</div><div>1 ~ 9</div><div>1 ~ 6</div></div><div>+</div><div><div>End Cap Length</div><div>10mm</div></div></div> <div><div><div>Cross-sectional sizes when installed with FAS00-01TDA or FATDA-HA</div><div><div><div>30.8</div><div>27.3</div></div><div><div>When mounting the channels, ensure space of 10mm for both left and right.</div></div></div><div><div><div>70</div><div>29</div><div>70</div></div><div><div>6</div><div>3</div><div>4</div><div>7</div></div></div><div><div><div>26.3</div><div>21.7</div><div>18.2</div></div><div><div>5</div><div>2</div><div>1</div></div><div><div>X-X' Section</div></div></div><div><div><div>24.5</div><div>23.8</div></div></div></div><div><div><div>General tolerance</div><div>Cross-sectional direction</div><div>6 or below: ±1.0</div><div>6 to 15 or below: ±1.2</div><div>15 to 30 or below: ±1.6</div><div>30 to 50 or below: ±2.0</div></div><div><div>Tolerance values are based on 25 °C.</div><div><div>Length(m)</div><div>~1</div></div><div><div>Tolerance(mm)</div><div>+10 ~ -10</div></div></div><div><div>※When connecting products and power supplies in parallel in multiple systems, make sure that the types and lengths of the wires in each system are the same to prevent differences in brightness and color between the products.</div><div>(Unit: mm)</div></div></div><table><tr><th colspan="4">Product Specifications</th><th>7</th><th>Output Cable</th><th>Silicone rubber coating</th><th>Waterproof Connector (FWS series, 4pin) AWG22 / Red(24V), White(DO+), Green(DO+), Black(GND)</th><th colspan="3">3D image</th></tr><tr><td>Pitch Type</td><td>Fine Pitch</td><td>Standard Pitch</td><td>Long Pitch</td><td>6</td><td>Input Cable</td><td>Silicone rubber coating</td><td>Waterproof Connector (FWS series, 4pin) AWG22 / Red(24V), White(DI+), Green(DI+), Black(GND)</td><td colspan="3" rowspan="15"></td></tr><tr><td>Product No.</td><td>TLD10-ADR-F</td><td>TLD10-ADR-S</td><td>TLD10-ADR-L</td><td>5</td><td>Filler</td><td>Silicone rubber</td><td>Clear</td></tr><tr><td>Length</td><td colspan="2">114 mm ~ 1026mm + End-caps 10mm</td><td>171mm ~ 1026mm + End-caps 10mm</td><td>4</td><td>End cap</td><td>Silicone rubber</td><td>Translucent</td></tr><tr><td>Weight</td><td colspan="3">340 g/m</td><td>3</td><td>Case</td><td>Silicone rubber</td><td>Translucent</td></tr><tr><td>Input Voltage</td><td colspan="3">DC24V</td><td>2</td><td>Color LED</td><td>SMD LED</td><td></td></tr><tr><td>Power Consumption</td><td>13W/m</td><td colspan="2">12W/m</td><td>1</td><td>FPC</td><td>Polyimide</td><td>Flexible Printed Circuits</td></tr><tr><td>Color</td><td colspan="3">Red, Green, Blue</td><th colspan="2">Parts Name</th><th>Material</th><th>Note</th></tr><tr><td>Luminous Flux</td><td colspan="3">Red:110 lm/m, Green:260 lm/m, Blue:50 lm/m</td><th colspan="4">Parts List</th></tr><tr><td>Beam Angle</td><td colspan="3">160°</td><th colspan="4">Accessories (Option)</th></tr><tr><td>Bending Radius</td><td colspan="3">R150 mm Vertical</td><td>1</td><td>Aluminum Rigid Channel</td><td>FAS00-01TDA</td><td>Length=1000mm</td></tr><tr><td>Dimming Signal Standard</td><td colspan="3">DMX512 Standard</td><td>2</td><td>Aluminum Mounting Bracket</td><td>FATDA-HA</td><td>Length=36mm Including spring 5pcs per pack Please use 5pcs per meter.</td></tr><tr><td>Compatible DMX Controller</td><td colspan="3">DMX Controller Conforming to DMX512 Standard * Please contact our sales for recommended models.</td><td>3</td><td>DMX Input Cable for XLR3</td><td>WCADR-XLR3S</td><td>Length=1000mm waterproof type except XRL3</td></tr><tr><td rowspan="2">DMX Address</td><td colspan="3" rowspan="2">From the beginning, 1ch: R / 2ch: G / 3ch: B ... will be addressed automatically. When concatenated, DMX addresses will be consecutive from the unit in front.</td><td>4</td><td>DMX Input Cable for XLR5</td><td>WCADR-XLR5S</td><td>Length=1000mm waterproof type except XRL5</td></tr><tr><td>5</td><td>DMX Input Cable for RJ45</td><td>WCADR-RJ45S</td><td>Length=1000mm waterproof type except RJ45</td></tr><tr><td>DMX Control Length</td><td>57mm Unit</td><td>114mm Unit</td><td>171mm Unit</td><td>6</td><td>DC/DMX Input Cable</td><td>WCADR-DCDMXIN</td><td>Waterproof type except cable (red, black)</td></tr><tr><td>Used DMX Channels</td><td>54 channels / m</td><td>27 channels / m</td><td>18 channels / m</td><td>7</td><td>DMX Output Cable</td><td>WCADR-DMXOUT</td><td>Waterproof type</td></tr><tr><td>Maximum DMX Control Length ※1</td><td>9,690mm</td><td>19,380mm</td><td>29,070mm</td><td>8</td><td>DMX Relay Cable</td><td>WCADR-DMXRC3S</td><td>Length=1000mm waterproof type</td></tr><tr><td>Max Unit Connectable ※2</td><td>5180mm (1036mm x 5pcs)</td><td colspan="2">* If you connect more products, the brightness and color will vary greatly.</td><td>9</td><td>DC/DMX Relay Cable</td><td>WCADR-4CR</td><td>Length=1000mm waterproof type</td></tr><tr><td>Ambient temperature and humidity</td><td>Environment</td><td>-10 ~ 55℃ , 45 ~ 85% RH</td><td>Indoor / Outdoor (IP67 rated)</td><td>10</td><td>Waterproof termination connector</td><td>WCADR-4TC</td><td>Waterproof type</td></tr></table><table><tr><td></td><td>Drawn</td><td>Reviser</td><td>Approved</td></tr><tr><td></td><td>Kawasaki</td><td></td><td>Tanimizu</td></tr><tr><td></td><td>2025.10.9</td><td></td><td>2025.10.9</td></tr></table></div>											Product Specifications				7	Output Cable	Silicone rubber coating	Waterproof Connector (FWS series, 4pin) AWG22 / Red(24V), White(DO+), Green(DO+), Black(GND)	3D image			Pitch Type	Fine Pitch	Standard Pitch	Long Pitch	6	Input Cable	Silicone rubber coating	Waterproof Connector (FWS series, 4pin) AWG22 / Red(24V), White(DI+), Green(DI+), Black(GND)				Product No.	TLD10-ADR-F	TLD10-ADR-S	TLD10-ADR-L	5	Filler	Silicone rubber	Clear	Length	114 mm ~ 1026mm + End-caps 10mm		171mm ~ 1026mm + End-caps 10mm	4	End cap	Silicone rubber	Translucent	Weight	340 g/m			3	Case	Silicone rubber	Translucent	Input Voltage	DC24V			2	Color LED	SMD LED		Power Consumption	13W/m	12W/m		1	FPC	Polyimide	Flexible Printed Circuits	Color	Red, Green, Blue			Parts Name		Material	Note	Luminous Flux	Red:110 lm/m, Green:260 lm/m, Blue:50 lm/m			Parts List				Beam Angle	160°			Accessories (Option)				Bending Radius	R150 mm Vertical			1	Aluminum Rigid Channel	FAS00-01TDA	Length=1000mm	Dimming Signal Standard	DMX512 Standard			2	Aluminum Mounting Bracket	FATDA-HA	Length=36mm Including spring 5pcs per pack Please use 5pcs per meter.	Compatible DMX Controller	DMX Controller Conforming to DMX512 Standard * Please contact our sales for recommended models.			3	DMX Input Cable for XLR3	WCADR-XLR3S	Length=1000mm waterproof type except XRL3	DMX Address	From the beginning, 1ch: R / 2ch: G / 3ch: B ... will be addressed automatically. When concatenated, DMX addresses will be consecutive from the unit in front.			4	DMX Input Cable for XLR5	WCADR-XLR5S	Length=1000mm waterproof type except XRL5	5	DMX Input Cable for RJ45	WCADR-RJ45S	Length=1000mm waterproof type except RJ45	DMX Control Length	57mm Unit	114mm Unit	171mm Unit	6	DC/DMX Input Cable	WCADR-DCDMXIN	Waterproof type except cable (red, black)	Used DMX Channels	54 channels / m	27 channels / m	18 channels / m	7	DMX Output Cable	WCADR-DMXOUT	Waterproof type	Maximum DMX Control Length ※1	9,690mm	19,380mm	29,070mm	8	DMX Relay Cable	WCADR-DMXRC3S	Length=1000mm waterproof type	Max Unit Connectable ※2	5180mm (1036mm x 5pcs)	* If you connect more products, the brightness and color will vary greatly.		9	DC/DMX Relay Cable	WCADR-4CR	Length=1000mm waterproof type	Ambient temperature and humidity	Environment	-10 ~ 55℃ , 45 ~ 85% RH	Indoor / Outdoor (IP67 rated)	10	Waterproof termination connector	WCADR-4TC	Waterproof type		Drawn	Reviser	Approved		Kawasaki		Tanimizu		2025.10.9		2025.10.9
Product Specifications				7	Output Cable	Silicone rubber coating	Waterproof Connector (FWS series, 4pin) AWG22 / Red(24V), White(DO+), Green(DO+), Black(GND)	3D image																																																																																																																																																																																
Pitch Type	Fine Pitch	Standard Pitch	Long Pitch	6	Input Cable	Silicone rubber coating	Waterproof Connector (FWS series, 4pin) AWG22 / Red(24V), White(DI+), Green(DI+), Black(GND)																																																																																																																																																																																	
Product No.	TLD10-ADR-F	TLD10-ADR-S	TLD10-ADR-L	5	Filler	Silicone rubber	Clear																																																																																																																																																																																	
Length	114 mm ~ 1026mm + End-caps 10mm		171mm ~ 1026mm + End-caps 10mm	4	End cap	Silicone rubber	Translucent																																																																																																																																																																																	
Weight	340 g/m			3	Case	Silicone rubber	Translucent																																																																																																																																																																																	
Input Voltage	DC24V			2	Color LED	SMD LED																																																																																																																																																																																		
Power Consumption	13W/m	12W/m		1	FPC	Polyimide	Flexible Printed Circuits																																																																																																																																																																																	
Color	Red, Green, Blue			Parts Name		Material	Note																																																																																																																																																																																	
Luminous Flux	Red:110 lm/m, Green:260 lm/m, Blue:50 lm/m			Parts List																																																																																																																																																																																				
Beam Angle	160°			Accessories (Option)																																																																																																																																																																																				
Bending Radius	R150 mm Vertical			1	Aluminum Rigid Channel	FAS00-01TDA	Length=1000mm																																																																																																																																																																																	
Dimming Signal Standard	DMX512 Standard			2	Aluminum Mounting Bracket	FATDA-HA	Length=36mm Including spring 5pcs per pack Please use 5pcs per meter.																																																																																																																																																																																	
Compatible DMX Controller	DMX Controller Conforming to DMX512 Standard * Please contact our sales for recommended models.			3	DMX Input Cable for XLR3	WCADR-XLR3S	Length=1000mm waterproof type except XRL3																																																																																																																																																																																	
DMX Address	From the beginning, 1ch: R / 2ch: G / 3ch: B ... will be addressed automatically. When concatenated, DMX addresses will be consecutive from the unit in front.			4	DMX Input Cable for XLR5	WCADR-XLR5S	Length=1000mm waterproof type except XRL5																																																																																																																																																																																	
				5	DMX Input Cable for RJ45	WCADR-RJ45S	Length=1000mm waterproof type except RJ45																																																																																																																																																																																	
DMX Control Length	57mm Unit	114mm Unit	171mm Unit	6	DC/DMX Input Cable	WCADR-DCDMXIN	Waterproof type except cable (red, black)																																																																																																																																																																																	
Used DMX Channels	54 channels / m	27 channels / m	18 channels / m	7	DMX Output Cable	WCADR-DMXOUT	Waterproof type																																																																																																																																																																																	
Maximum DMX Control Length ※1	9,690mm	19,380mm	29,070mm	8	DMX Relay Cable	WCADR-DMXRC3S	Length=1000mm waterproof type																																																																																																																																																																																	
Max Unit Connectable ※2	5180mm (1036mm x 5pcs)	* If you connect more products, the brightness and color will vary greatly.		9	DC/DMX Relay Cable	WCADR-4CR	Length=1000mm waterproof type																																																																																																																																																																																	
Ambient temperature and humidity	Environment	-10 ~ 55℃ , 45 ~ 85% RH	Indoor / Outdoor (IP67 rated)	10	Waterproof termination connector	WCADR-4TC	Waterproof type																																																																																																																																																																																	
	Drawn	Reviser	Approved																																																																																																																																																																																					
	Kawasaki		Tanimizu																																																																																																																																																																																					
	2025.10.9		2025.10.9																																																																																																																																																																																					

※1: Maximum total fixture length connectable to a single DMX512 controller.
 ※2: Maximum total fixture length connectable in series to a single power supply.
 Please note that content described above may be changed without any advance notice