













### **ORDERING**

#### **PRODUCT No.**

PRODUCT No.				LENGTH		
TMV	30	-	10	27K		10099
1	2		3	4	5	6
PRODUCT	OUTPUT		lm	LED COLOR	LEAD WIRES	LENGTH

#### **PRODUCT**

### **OUTPUT**

30 LED 28.5mm pitch

3	lm		
	10	1000 lm/m	
	06	600 lm/m	

# 4 LED COLOR

22K	2200K	
27K	2700K	
30K	3000K	
35K	3500K	
40K	4000K	
50K	5000K	

### Lead wires at one end.

Lead wires at both ends.

# LENGTH

**LEAD WIRES** 

**5054.5** 5054.5 mm **10099** 10099mm

### **KEY FEATURES AND BENEFITS**

- 6 color variation
- Max length 10099mm
- Affordable VE type.
- Cuttable at site and easy customize
- Top-Bend
- Clear type
- Optimum item for Indirect Lighting
- LEDs covered by Silicone Case
- Installation : See ACCESSORIES for options on mounting channels and brackets.
- Environment: Interior, dry location use only.
- **LED**: 3 step MacAdam ellipses
- Power and Control: DMX-512, on/off, and dimming control options. Contact factory for more information.

# **PRODUCT SPECIFICATIONS**

	1000 lm type	600 lm type	
2200K	1010 lm/m	570 lm/m	
2700K	980 lm/m	590 lm/m	
3000K	1000 lm/m	600 lm/m	
3500K	1020 lm/m	610 lm/m	
4000K	1060 lm/m	640 lm/m	
5000K	1060 lm/m	640 lm/m	
WATTS	11 W/m	6 W/m	
LED PITCH	28.5 mm		
TRIM POINTS	Every 85.5 mm		
INPUT	24VDC ±1V		
WIDTH 1	15 mm		
HEIGHT 1	5 mm		
LENGTH	5054.5 mm or 10099mm		
WEIGHT	85g per meter		
BEAM ANGLE	110°		
Max Unit Connectable	10099 mm		
<b>Bending Radius</b>	30 mm vertical		
Operating Temperature	-10° to 40° C		
Find can is 17w v 7h mm (11/16 v 1// in) See DRAWINGS			


<sup>&</sup>lt;sup>1</sup> End cap is 17w x 7h mm (11/16 x 1/4 in). See DRAWINGS.

#### PRODUCT No.

1000 lm type	600 lm type	LED COLOR
TMV30-1022K	TMV30-0622K	2200K
TMV30-1027K	TMV30-0627K	2700K
TMV30-1030K	TMV30-0630K	3000K
TMV30-1035K	TMV30-0635K	3500K
TMV30-1040K	TMV30-0640K	4000K
TMV30-1050K	TMV30-0650K	5000K



### **DIMENSIONS**



# ACCESSORIES 1





### **POLYCARBONATE MOUNTING BRACKET**

☐ FJB00-21(Qty:5pcs per pack)

Mounting bracket for securing Tape Light to any surface with screws (supplied by others).

Clear polycarbonate. Please use 5pcs per meter.

Weight: 0.25g/PC

W x H x L : 37.6 x 7 x 10 mm

 $Select \ one \ method \ for \ installation. \ These \ accessories \ are \ not \ used \ together. \ See \ INSTALLATION.$ 

CAPILO